

MODEL VA1


Seamless switching between any source Free customized among 2.5 million Plug & Play USB Media Player EDID Management Open Protocol Control Two Sending Card Slot Built-in Signal Hot Backup Audio & Video Sync Switching



PRODUCT APPLICATIONS


Application 1: Customized Input & Output Resolution for Pixel by Pixel Display

VA1 Support customized output resolution. Compatible with any LED screen size within 2K. Use EDID Management to configure input resolution. Realize Pixel by Pixel Display without any stretch or compression.



Application 2: Play Video & Image Content Via USB with 6 Transition Feature

VA1 has hot-swap USB port on both front and back panel. Support up to 6 transition effects among video and image media files.



Application 3: Audio & Video Sync Switching

De-embedded audio from HDMI DVI and USB player. Support audio & video sync switching with 3.5mm audio jack.





FEATURES

Plug & play USB Media Player

VA1 has USB port on both front and back panel. Support both image and video media files.



rm,rmvb,mp4, mov,mkv,wmv,avi,3gp
.jpg .jpeg .png .bmp

Signal Hot Backup


Support DVI-HDMI hot backup. VA1 support auto switch when encountered input signal issue.



SPECIFICATIONS

Seamless switching

Seamless switching between any input channel



AV Sync Switching

Support HDMI DVI USB audio & video switching with 3.5mm audio jack output.



Inputs	Standard	1 × DVI / 1 x HDMI / 2 x USB		
	Optional	1 × VGA / 1x CVBS 1 × SDI + LOOP		
Outputs	Standard 2 × DVI			
		1 x 3.5mm audio jack		
Operation	Front panel+RS232/USB Open Protocol Control			
Input format	DVI	VESA: 800x600 1024x768 1280x1024 1600x1200 1920x1080 1920x1200 2048x1152		
	HDMI	SMPTE: 480i 576i 720p 1080i 1080p VESA: 800x600 1024x768 1280x720 1280x800 1280x960 1280x1024 1400x1050 1600x1200 1920x1080 1920x1200 2048x1152		
	VGA	800x600 1024x768 1280x1024 1600x1200 1920x1080 1920x1200		
	CVBS	SMPTE: 480i 576i		
	USB	Video: 720P rm rmvb mp4 mov mkv wmv avi 3gp Picture: jpg jpeg png bmp		
Output	SMPTE	720p 1080p		
format	VESA	1024x768 1280x720 1280x1024 1400x1050 1600x1200 1920x1080 1920x1200 2048x1152 2560x816 1024x1280 1152x1152 1280x1280 1536x1536		
Input	AC 100~264V (Typical110/220)			
Power	50/60Hz			
Max Power	20W			
TEMP	-25°C~55°C (Typical 25°C)			
HUM	20%~90%			
Weight	3.0kg (Device) 4.0kg (Packed)			
Dimensions	480mm x 265mm x 44mm (Device)			
	540mm x 365mm x 135mm (Packed)			
_	_			

Order Codes

Product Code	Model
P180-VA1-000-01	1U Scaler & Switcher with small button



XIAMEN SPROLINK SCIENCE & TECHNOLOGY CO., LTD

Unit 301,No.1734,Gangzhong Road, Xiamen Free Trade Zone,China.
sales@sprolink.com
+86 592 556 5698
www.sprolink.com

